SUBSTITUTE SPECIFICATION: CLEAN COPY

METHOD FOR AUTOMATICALLY DETERMINING THE INSTALLATION POSITIONS OF
WHEELS IN A MOTOR VEHICLE

BACKGROUND OF THE INVENTION

[0001]   The present invention relates to a method for the
automatic determination of the installation positions of wheels in
a motor vehicle.

[0002]   DE 42 05 911 A1 discloses a monitoring device for the
air pressure of tires of vehicle wheels. However, the realization
presented therein is very sophisticated. An embodiment mentioned
therein includes an associated receiver on the vehicle for each
transmitter in the wheel, while another embodiment is based on a
combined transmitting/ receiving unit in the wheel and one or more
receiving units on the vehicle. The individual wheels are
allocated to their installation positions by way of a so-called
pairing process, which is carried out either manually or
automatically. In the manual pairing process, an operator
allocates the wheels to their installation positions. Therefore,
the manual pairing process is very time-consuming and labor-
intensive and, in the event of a faulty operation, can cause a
wrong allocation of the individual wheels to their installation
positions. The automatic pairing process renders a correct
allocation of the individual wheels to the installation positions
possible. However, the technical effort needed is very
comprehensive and costly as it necessitates additional hardware,
e.g. several receiving antennas.

[0003]   DE 197 21 480 A1 discloses a method for detecting
pressure loss in the vehicle tire. As the method is based on
signals being obtained from rotational wheel speeds of several

AP10587   1

vehicle wheels, it is possible to allocate the wheel with air
pressure loss to the respective, actually existing mounting
position. However, the method is inappropriate to determine an
absolute pressure value of the individual wheels.

SUMMARY OF THE INVENTION

[0004]   In view of the above, an object of the invention
involves providing a low-cost method, which furnishes data about
absolute air pressure values and the mounting positions.

[0005]   This object is achieved by means of the method for the
automatic determination of the installation position of wheels in
a motor vehicle. The method includes receiving tire pressure
monitoring system data (TPMS) from a direct measure tire pressure
monitoring system, receiving deflation detection data from an
indirect tire pressure monitoring system and determining
correlation coefficients from the TPMS data and the deflation data
by means of a correlation function.

[0006]   The correlation coefficients are preferably determined
from first allocation functions and second allocation function by
using a correlation function.

[0007]   The first allocation functions are preferably produced
from the TPMS data describing all possible allocations of the
identification numbers to the installation positions, and an
individual characteristic value is allocated to each possible
allocation. Further, in the preferred embodiment described herein,
the second allocation functions are produced from the DDS data
assigning in each case another individual characteristic value to
each possible installation position of a wheel. Preferably, the

first allocation functions are composed of 24 functions $F\_dmR\_j\_i$ (j describes an integral index which can assume values between 1 and 24; i describes a consecutive index), which describe all possible allocations of the identification numbers to the installation positions in a four-wheel vehicle. In a furthermore preferred manner, the second allocation functions in a four-wheel vehicle are composed of four functions F_imR_i (i describes another consecutive index), which describe the possible installation positions (left front, right front, left rear, right rear).

[0008]   In another preferred embodiment of the current method, the correlation function comprises an averaging operation as a function of time.

[0009]   Preferably, the correlation function is obtained from a quotient, from a dividend essentially composed of a multiplication of the first allocation functions with the second allocation functions, and a divisor essentially composed of a multiplication of the squared first allocation functions with the squared second allocation functions.

[0010]   In another preferred embodiment, the correlation coefficients represent numerical values describing probabilities, whether the selected allocation of the identification numbers to the installation positions is coincident with the actual allocation, while the time averaging operation causes a standardization of the numerical values to a range of values, in particular to a range between -1 and +1.

[0011]   Advantageously, all calculated correlation coefficients are compared with each other, and the correlation coefficient with the maximum absolute numerical value irrespective of sign

AP10587   3

represents the correct allocation of the wheels to the installation positions. Subsequently, the identification numbers are allocated to the installation positions according to the determined allocation.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0012]   Further preferred embodiments can be taken the following description of an embodiment.

[0013]   The method is based on a direct measuring tire pressure monitoring system (TPMS; Tire Pressure Monitoring System) with four transmitting wheel pressure modules and a receiving and evaluating device. In this system each wheel is equipped with a tire pressure measuring device including a transmitting device which transmits TPMS data to the receiving and evaluating device, said data being composed for each wheel of a wheel-related identification number and the air pressure pertaining to this wheel. Since the directly measuring tire pressure monitoring system described above, without a pairing process described hereinabove or any other allocation process, is not in a position to realize an allocation of the wheels to their installation positions merely by way of the identification numbers, further information is required that allows allocating the wheels to their installation positions. This additional information, hereinbelow referred to as DDS data, is obtained from an indirectly measuring tire pressure monitoring system (DDS; Deflation Detection System), which determines changes in the air pressure from the rotational behavior of the individual wheels and is therefore appropriate to determine the installation position of a wheel exhibiting pressure loss. The directly measuring tire pressure monitoring system

transmits the TPMS data to the receiving and evaluating device. The indirectly measuring tire pressure monitoring system preferably produces reference values being indicative of tire pressure loss. The TPMS data is changing during driving, more or less constantly, e.g. due to the influence of temperature. DDS data is also influenced during driving due to numerous disturbing effects such as changing rolling circumferences of the wheel on account of wheel load variations, changes in the coefficient of friction, load variations, etc. The method of the invention is based on the fact that in a case of control the tire pressure changes of the TPMS data correlate with the changes of the DDS data.

[0014]   According to the method of the invention, two allocation functions F_imR (imR refers to the indirectly measuring tire pressure monitoring system) and F_dmR (dmR refers to the directly measuring tire pressure measuring system), which allow an allocation of the wheels to the installation positions by means of a correlation method and an evaluating method.

[0015]   The function F_imR_i (i refers to a consecutive index) assigns a value to a wheel. As this occurs,

F_imR_i = 1, if wheel VR (right front) is faster,

F_imR_i = 2, if wheel VL (left front) is faster,

F_imR_i = 3, if wheel HL (left rear) is faster,

F_imR_i = 4, if wheel HR (right rear) is faster.

[0016]   In this arrangement VR means right front, VL means left front, HL means left rear, and HR means right rear.

[0017]   Since the direct measuring tire pressure monitoring system transmits only an information about the absolute tire air

pressure and the associated identification number ID_x (x refers to an integral index from 1 to 4), all possible combinations between the installation positions (VR, VL, HR, HL) and the identification numbers (ID_1, ID_2, ID_3, ID_4) must be tested. 24 different combinations result in a four-wheel vehicle. These 24 functions F_dmR_j_i (j describes an integral index that can adopt values between 1 and 24; i describes a consecutive index) are calculated in the following. The first function F_dmR_1_i e.g. corresponds to the possible allocation:

VR = ID_1, VL = ID_2, HL = ID_3, HR = ID_4.

[0018]   From this results the following allocation of values for the function F_dmR_1_i:

F_dmR_1_i = 1,   if the wheel with ID_1 has the higher rate of pressure reduction,

F_dmR_1_i = 2,   if the wheel with ID_2 has the higher rate of pressure reduction,

F_dmR_1_i = 3,   if the wheel with ID_3 has the higher rate of pressure reduction, and

F_dmR_1_i = 4,   if the wheel with ID_4 has the higher rate of pressure reduction.

[0019]   The second function F_dmR_2_i e.g. corresponds to the possible allocation VR = ID_2, VL = ID_3, HL = ID_4, HR = ID_1.

[0020]   The following allocation of values results from this for the function F_dmR_2_i:

F_dmR_2_i = 1,   if the wheel with ID_2 has the higher rate of pressure reduction,

F_dmR_2_i = 2,   if the wheel with ID_3 has the higher
rate of pressure reduction,

F_dmR_2_i = 3,   if the wheel with ID_4 has the higher
rate of pressure reduction, and

F_dmR_2_i = 4,   if the wheel with ID_1 has the higher
rate of pressure reduction.

[0021]   Corresponding values are allocated to the functions
F_dmR_3_i to F_dmR_24_i.

[0022]   The 24 correlation coefficients Korr_j (j describes an
integral index, which can adopt values between 1 und 24) are
determined according to the equation

$$Korr\_j = \frac{\sum\limits_{i=1}^{N}[(F\_imR\_i)\bullet(F\_dmR\_j\_i)]-\frac{1}{N}\bullet\sum\limits_{i=1}^{N}(F\_imR\_i)\bullet\sum\limits_{i=1}^{N}(F\_dmR\_j\_i)}{\left\{\left[\left(\sum\limits_{i=1}^{N}(F\_imR\_i)^2\right)-\frac{1}{N}\bullet\left(\sum\limits_{i=1}^{N}F\_imR\_i\right)^2\right]\bullet\left[\left(\sum\limits_{i=1}^{N}(F\_dmR\_j\_i)^2\right)-\frac{1}{N}\bullet\left(\sum\limits_{i=1}^{N}F\_dmR\_j\_i\right)^2\right]\right\}^{0,5}}$$

N indicates the number of measurements.

[0023]   The correlation coefficients Korr_j are in the range -1
≤ Korr_j ≤ +1. The function F_dmR_j_i, having a correlation
coefficient Korr_j whose absolute value irrespective of sign is
considerably higher than all other correlation coefficients
Korr_j, describes with a high rate of probability the correct
allocation of the identification numbers (ID_1, ID_2, ID_3, ID_4)
to their installation positions (VL, VR, HL, HR).
The allocation of the function F_dmR_1_i with VR = ID_1, VL =
ID_2, HL = ID_3, HR = ID_4 e.g. describes the correct allocation.
This means that the correlation coefficient Korr_1 has a

considerably higher absolute value irrespective of sign than the other calculated correlation coefficients.